

Flash Duplicator

CPY220
CopyKing II



CPY220USB
20 USB Port Flash Duplicator



CPY220SD
20 SD Port Flash Duplicator



CPY220MSD
20 microSD Port Flash Duplicator



CPY220COMBO
20 USB/SD/microSD Port Flash Duplicator



Changeable Module

Warranty and Maintenance


- Warranty: 1 year after delivery date
- Maintenance: provide I/O Board module for replacement if damaged by massive usage

CPY220USB IO



CPY220 4-port USB IO Module

CPY220SD IO



CPY220 4-port SD IO Module

CPY220MSD IO



CPY220 4-port microSD IO Module

CARDCOPY

Unit 6c, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU, UK
CardCopy is a trading division of Cardwave Services Ltd.
Tel: +44 (0)1380 738395
Email: sales@cardcopy.eu
Web: www.cardcopy.eu

CPY220

CopyKing II

Features:

- Duplicate 20 USB flash drive or 20 SD cards or 20 microSD cards simultaneously
- Up to 20MB/sec duplication per port
- Standalone or PC management via network
- CopyMan, PC central control software to:
 - Manage up to 200 pieces of CPY220
 - Assign different tasks to multiple duplicators simultaneously
 - Generate log file
- Clone Copy to clone Phison USB controller-based flash drives' various partition configurations from master to targets, including:
 - CD-ROM drive
 - DVD+RW drive
- Support ReadOnly & ClearOnly of Phison USB flash drive
- Support CPRM Copy of SD/MSD cards (optional)
- MP Tool for mass initialization of Phison controller-based USB flash drive
- Changeable I/O module - easy maintenance & cost saving

Hardware Information:

Models		CPY220USB (Lite)	CPY220SD (Lite)	CPY220MSD (Lite)	CPY220USB	CPY220SD	CPY220MSD	CPY220COMBO
Hardware Information	Master Port	1 USB	1 SD	1 microSD	1 USB	1 SD	1 microSD	1 USB, 1 SD
	Target Port	20 USBs	20 SDs	20 microSDs	20 USBs	20 SDs	20 microSDs	20 USBs / 20 SDs / 20 microSD
	Support Media	USB	SD, SDHC, Mini SD, microSD	microSD	USB	SD, SDHC, Mini SD, microSD	microSD	USB, SD, SDHC, Mini SD, microSD
	Operating Type	Standalone			Standalone or PC			
	Maximum Copy Speed	Up to 20MB/ sec			Up to 20MB/ sec			
	Hard Disk Drive	N/A			250GB			
	Display	3.5" TFT LCD			3.5" TFT LCD			
	Control Button	Power/Up/Down/ESC/OK			Power/Up/Down/ESC/OK			
	Indicator	Red: Error (Static) Red: In Progress (Blinking) Green: Pass			Red: Error (Static) Red: In Progress (Blinking) Green: Pass			
	I/O Board	Changeable module (4 ports per module)			Changeable module (4 ports per module)			
	Power Supply	200W, 100V~240VAC input			200W, 100V~240VAC input			
	Power Consumption	Standby: 47W Full Operation: 109W			Standby: 47W Full Operation: 109W			
	Dimension/Weight(Net)	220mm x 219 x 286 (L x W x H) / 5.2kg			220mm x 219 x 286 (L x W x H) / 5.36kg			
	Network	10/100Mbps			10/100Mbps			
	PC OS	N/A			Windows XP			
Safety	RoHS, FCC, CE			RoHS, FCC, CE				

Specification subject to change without notice